

NATIONAL ADVISORY COMMITTEE FOR AERONAUTICS

TECHNICAL NOTE NO. 1326

AIRFOIL IN SINUSOIDAL MOTION

IN A PULSATING STREAM

By J. Mayo Greenberg

SUMMARY

The forces and moments on a two-dimensional airfoil executing harmonic motions in a pulsating stream are derived on the basis of nonstationary incompressible potential-flow theory, with the inclusion of the effect of the continuous sheet of vortices shed from the trailing edge. An assumption as to the form of the wake is made with a certain degree of approximation. A comparison with previous work applicable only to the special case of a stationary airfoil is made by means of a numerical example and the excellent agreement obtained shows that the wake approximation is quite sufficient. The results obtained are expected to be useful in considerations of forced vibrations and flutter of rotary-wing aircraft for which the lifting surfaces are in air streams of variable velocity.

INTRODUCTION

The problem of an airfoil in arbitrary motion in a pulsating stream arises in connection with rotating blades in forward motion, for example, helicopter blades. Use of two-dimensional theory for this problem leads to deviations from reality with respect to the position of the wake, but, as most of the wake effects arise from that part near the airfoil, the error should not be serious.

Restricted results, applicable to an airfoil at a fixed angle of attack in a pulsating stream, have been obtained by Isaacs (reference 1). In the present paper, under the same linearizing assumptions as are made in the derivation in reference 1 but with explicit consideration and simplification of the form of the wake extending from the rear of the airfoil, the methods of Theodorsen (reference 2) have been extended to obtain the forces on the airfoil not only at a fixed angle of attack but also in arbitrary motion. The result is in closed form as compared with the Fourier series result of reference 1. Inclusion of the effects of arbitrary motion

June 1947

24
 nd
 se
 1-1-47

of the airfoil presents the possibility of application to forced vibrations and to flutter of helicopter blades.

SYMBOLS

a'	position of torsion axis of wing measured from center
a	nondimensional position of torsion axis of wing measured from center
b	half chord of wing
α	fixed part of angle of attack measured clockwise from horizontal
β	varying part of angle of attack
h	vertical displacement, positive downward
x'	horizontal coordinate
x	nondimensional coordinate
t	time
v	stream velocity
ν	frequency
ω	circular frequency ($2\pi\nu$)
$k = \frac{\omega b}{v}$	reduced frequency
$C(k) = F + iG$	C function (reference 2)
$\delta(x)$	Dirac delta function (reference 3)
p	local static pressure
ρ	air density
σ	a number determining magnitude of stream pulsations
P	perpendicular force
M_a	pitching moment about $x = a$, positive counter clockwise

 ϕ ϕ_T U ψ $\Delta\Gamma$

Subsc

 α β v h 0

force
wake
incom
small
infin

chord
havin
angle
attac
allow
 β (t
the t
norma

ϕ	noncirculatory velocity potential
ϕ_T	circulatory velocity potential
U	strength of wake discontinuity
ψ	phase angle with respect to stream pulsations
$\Delta\Gamma$	element of vorticity

Subscripts:

α	fixed part of angle of attack
β	varying part of angle of attack
v	stream velocity
h	vertical displacement
0	with β or h , maximum amplitude; with x , wake position; with v , steady part

DERIVATION OF FORCES

Method.- In a derivation parallel to that of reference 2, the forces due to the noncirculatory flow and to the effect of the wake are treated separately, the usual assumptions being made: incompressible potential flow, two-dimensional flat-plate airfoil, small oscillations, and plane wake extending from trailing edge to infinity.

Noncirculatory force and moment.- Consider an airfoil of chord $2b$ at an angle of attack $\alpha + \beta$ with respect to a stream having velocity v directed to the right (fig. 1). Let the angle α be constant so that the only variation in angle of attack is due to a variation in the angle β . If the airfoil is allowed to rotate about the point $x' = a'$ with angular velocity $\dot{\beta}$ (the dot over a symbol denotes differentiation with respect to the time t) and to move downward with a velocity h , the velocity normal to the airfoil is

$$\epsilon(x') = -\dot{h} - (\alpha + \beta)v + \dot{\beta}(a' - x')$$

The potential for such a normal velocity function is (see reference 2)

$$\phi = hb \sqrt{1-x^2} + v(\alpha + \beta)b \sqrt{1-x^2} + \beta b^2 \left(\frac{1}{2}x - a\right) \sqrt{1-x^2} \quad (1)$$

where

$$x = \frac{x'}{b}$$

$$a = \frac{a'}{b}$$

Using the equation of motion for nonstationary flow

$$\frac{\partial w}{\partial t} = -\nabla \left(\frac{p}{\rho} + \frac{1}{2}w^2 \right) \Leftrightarrow \frac{\partial \phi}{\partial t} + \frac{w^2}{2} + \frac{p}{\rho} = \frac{w_{\infty}^2}{2} + \frac{p_{\infty}}{\rho}$$

where

p local static pressure

ρ air density

w local velocity

and substituting

$$w = v + \frac{\partial \phi}{\partial x} \quad \phi: \text{perturbed velocity pot.}$$

gives the pressure difference at the point x as

$$\Delta p = -2\rho \left(\frac{v}{b} \frac{\partial \phi}{\partial x} + \frac{\partial \phi}{\partial t} \right) \quad (2)$$

Integration of this local pressure difference over the length of the airfoil gives as the total force

$$P = -\pi \rho b^2 \left[\bar{h} + v\beta + \dot{v}(\alpha + \beta) - ba\beta \right] \quad (3)$$

The noncirculatory moment about the point $x = a$ is

$$M_a = b^2 \int_{-1}^1 \Delta p(x - a) dx = -2\rho b^2 \int_{-1}^1 (x - a) \frac{\partial \phi}{\partial t} dx + 2\rho v b \int_{-1}^1 \frac{\partial \phi}{\partial x} dx \quad (1)$$

which becomes

$$M_a = -\pi \rho b^2 \left[-v^2(\alpha + \beta) - b a v(\alpha + \beta) - v h + b^2 \left(\frac{1}{\beta} + a^2 \right) \ddot{\beta} \right] \quad (3a)$$

h term? Ma

Circulatory force and moment. - The velocity potential of an element of vorticity $-\Delta\Gamma$ at a position x_0 in the wake and its image $\Delta\Gamma$ distributed over the airfoil is (reference 2)

$$\phi_{xx_0} = \frac{\Delta\Gamma}{2\pi} \tan^{-1} \frac{\sqrt{1-x^2} \sqrt{x_0^2-1}}{1-xx_0} \quad (4)$$


The element $-\Delta\Gamma$ moves to the right relative to the airfoil with a velocity v . Thus

$$\frac{\partial \phi_{xx_0}}{\partial t} = v \frac{\partial \phi_{xx_0}}{\partial x_0}$$

Substituting this expression and $\frac{\partial \phi_{xx_0}}{\partial x}$ into equation (2) and integrating the effect of the entire wake on the airfoil yields the force

$$P = -\rho v b \int_1^\infty \frac{x_0}{\sqrt{x_0^2-1}} U dx_0$$

$$= + \rho v b \int_1^\infty \frac{x_0}{\sqrt{x_0^2-1}} \gamma_w dx_0$$



where $U dx_0$ is the element of vorticity $\Delta\Gamma$ at the point x_0 .
The circulatory moment which is obtained from

$$M_a = b^2 \int_{-1}^1 \Delta p(x - a) dx$$

is, similarly,

$$M_a = -\rho v b^2 \int_1^{\infty} \left[\frac{1}{2} \sqrt{\frac{x_0 + 1}{x_0 - 1}} - \left(a + \frac{1}{2} \right) \frac{x_0}{\sqrt{x_0^2 - 1}} \right] U dx_0 \quad (5a)$$

The Kutta condition requires that at the trailing edge of the plate the induced velocity be equal to 0; therefore, at the point $x = 1$

$$\left[\frac{\partial}{\partial x^2} (\varphi_{\Gamma} + \varphi) \right]_{x=1} = 0$$

where

$$\varphi_{\Gamma} = b \int_1^{\infty} \varphi_{xx_0} dx_0$$

Introducing the potential from equation (1) results in

$$\frac{1}{2\pi} \int_1^{\infty} \sqrt{\frac{x_0 + 1}{x_0 - 1}} U dx_0 = \dot{h} + v(\alpha + \beta) + \dot{\beta} b \left(\frac{1}{2} - a \right) \quad (6)$$

The type of stream velocity encountered by a helicopter blade section in forward flight is

$$v = v_0 \left(1 + \sigma e^{i\omega_v t} \right) \quad (7)$$

where $\frac{2\pi}{\omega_v}$ is the period of pulsation of the stream. The assumption is made that $\sigma < 1$, because if $\sigma > 1$ there would occur a reversal of flow which cannot be treated by existing methods. In usual practice $\sigma > 1$ only for radial positions near the hub of a helicopter blade. For harmonic motions of the airfoil

$$\left. \begin{aligned} \beta &= \beta_0 e^{i(\omega_\beta t + \psi_\beta)} \\ h &= h_0 e^{i(\omega_h t + \psi_h)} \end{aligned} \right\} \quad (8)$$

where $\frac{2\pi}{\omega_\beta}$ and $\frac{2\pi}{\omega_h}$ are the periods of variation in angle of attack and in vertical displacement, respectively, and ψ_β and ψ_h are phase factors.

Equation (6) becomes, after substitution of equations (7) and (8),

$$\begin{aligned} \frac{1}{2\pi} \int_1^\infty \sqrt{\frac{x_0 + 1}{x_0 - 1}} U dx_0 &= v_0 \alpha + v_0 \sigma \alpha e^{i\omega_v t} \\ &+ \left[i\omega_\beta \beta_0 b \left(\frac{1}{2} - a \right) + v_0 \beta_0 \right] e^{i(\omega_\beta t + \psi_\beta)} \\ &+ i\omega_h h_0 e^{i(\omega_h t + \psi_h)} \\ &+ \sigma v_0 \beta_0 e^{i \left[(\omega_v + \omega_\beta) t + \psi_\beta \right]} \end{aligned} \quad (9)$$

(5a)

(6)

(7)

It is sufficient to satisfy the Kutta condition separately for each of the terms on the right-hand side of equation (9); therefore, a sheet of discontinuity of the following form is set up:

$$\begin{aligned}
 U = & \Gamma_{\alpha} \delta(\infty - x_0) + U_{\alpha} e^{i(\omega_v t - k_v x_0)} \\
 & + U_{\beta} e^{i(\omega_{\beta} t - k_{\beta} x_0)} + U_h e^{i(\omega_h t - k_h x_0)} \\
 & + U_{v+\beta} e^{i[(\omega_v + \omega_{\beta})t - k_{v+\beta} x_0]}
 \end{aligned}
 \tag{10}$$

Steady-state vortex which was shed long time ago is now at ∞ and localized there

This form matches well with eqn (9)

where $\delta(\infty - x_0)$ is the Dirac delta function (reference 3), and where

$$k_v = \frac{\omega_v b}{v_0}$$

$$k_{\beta} = \frac{\omega_{\beta} b}{v_0}$$

$$k_h = \frac{\omega_h b}{v_0}$$

$$k_{v+\beta} = \frac{(\omega_v + \omega_{\beta})b}{v_0}$$

Justification for assuming this form for the wake is given in the appendix.

Combining equations (9) and (10) and equating terms of corresponding time variation yields

$$\frac{1}{2\pi} \int_1^{\infty} \sqrt{\frac{x_0+1}{x_0-1}} \Gamma_{\alpha} \delta(\infty - x_0) dx_0 = v_0 \alpha$$

or $\Gamma_{\alpha} = 2\pi v_0 \alpha$ (the stationary circulation)

$$\frac{1}{2\pi v_1} \int_1^{\infty} \sqrt{\frac{x_0+1}{x_0-1}} U_{\alpha} e^{-ik_v x_0} dx_0 = \sigma v_0 \alpha$$

(10)

$$\frac{1}{2\pi v_1} \int_1^{\infty} \sqrt{\frac{x_0+1}{x_0-1}} U_{\beta} e^{-ik_{\beta} x_0} dx_0 = \left[i\omega_{\beta} \beta_0 b \left(\frac{1}{2} - a \right) + v_0 \beta_0 \right] e^{i\psi_{\beta}}$$

$$\frac{1}{2\pi} \int_1^{\infty} \sqrt{\frac{x_0+1}{x_0-1}} U_h e^{-ik_h x_0} dx_0 = i\omega_h h_0 e^{i\psi_h}$$

$$\frac{1}{2\pi} \int_1^{\infty} \sqrt{\frac{x_0+1}{x_0-1}} U_{v+\beta} e^{-ik_{v+\beta} x_0} dx_0 = \sigma v_0 \beta_0 e^{i\psi_{\beta}}$$

Introducing these relations and equation (10) into equation (5) gives

$$P = -2\pi \rho v b \left(v_0 \alpha + \sigma v_0 \alpha e^{i\omega_v t} \frac{\int_1^{\infty} \sqrt{\frac{x_0+1}{x_0-1}} U_{\alpha} e^{-ik_v x_0} dx_0}{\int_1^{\infty} \sqrt{\frac{x_0+1}{x_0-1}} U_{\alpha} e^{-ik_v x_0} dx_0} + \dots \right)$$

The quotient of integrals occurring in this expression is the C function defined in reference 2 as

$$C(k) = \frac{\int_1^{\infty} \frac{x_0}{\sqrt{x_0^2 - 1}} e^{-ikx_0} dx_0}{\int_1^{\infty} \frac{\sqrt{x_0 + 1}}{x_0 - 1} e^{-ikx_0} dx_0}$$

The force due to the wake is, therefore,

$$P = -2\pi\rho vb \left\{ v_0\alpha + \sigma v_0\alpha C(k_v) e^{i\omega_v t} \right. \\ + \left[i\omega_\beta\beta_0 b \left(\frac{1}{2} - a \right) + v_0\beta_0 \right] C(k_\beta) e^{i(\omega_\beta t + \psi_\beta)} \\ + i\omega_h h_0 C(k_h) e^{i(\omega_h t + \psi_h)} \\ \left. + \sigma v_0\beta_0 C(k_{v+\beta}) e^{i[(\omega_v + \omega_\beta)t + \psi_\beta]} \right\} \quad (11)$$

not correct (see Peters)

Applying the same methods to equation (5a) as were applied to equation (5) gives the moment due to the wake as

$$M_a = -\pi\rho vb^2 \left[\dot{h} + v(\alpha + \beta) + \dot{\beta} b \left(\frac{1}{2} - a \right) \right] \\ + 2\pi\rho vb^2 \left(a + \frac{1}{2} \right) \left\{ v_0\alpha + \sigma v_0\alpha C(k_v) e^{i\omega_v t} \right. \\ + \left[b \left(\frac{1}{2} - a \right) \dot{\beta} + v_0\beta \right] C(k_\beta) \\ \left. + \dot{h} C(k_h) + \sigma v_0\beta C(k_{v+\beta}) e^{i\omega_v t} \right\} \quad (11a)$$