Week 12 Bridge (1)

457.308 Construction Methods and Equipment Department of Civil and Environmental Engineering Seoul National University

> **Prof. Seokho Chi** <u>shchi@snu.ac.kr</u> 건설환경공학부 35동 304호

History of Bridge Development



History of Bridge Development



Bahrain's North Manama Causeway



How Bridges Work?

"Every passing vehicle shakes the bridge up and down, making waves that can travel at hundreds of kilometers per hour. Luckily the bridge is designed to damp them out, just as it is designed to ignore the efforts of the wind to turn it into a giant harp. A bridge is not a dead mass of metal and concrete: it has a life of its own, and understanding its movements is as important as understanding the static forces."



ABUTMENT

Basic Structure

Bearing to load of the top structure and acting as a retaining wall to soils



Basic Structure

- Bearing (교좌장치)
 - Transit loads from the top structure to the bottom structure
 - Resist to earthquake, wind (horizontal vibration), temperature changes (expansion and deflection/displacement)
- Expansion joint (신축이음장치)
 - Placing gaps to prepare for concrete expansion by temperature changes, concrete creep, dry shrinkage, and live load
 - Finger type and Rail type (이음새 고무 용착)









(a) finger type

(b) rail type



Basic Structure

• Drainage facility



• Maintenance facility (fixed and movable)



• Bridge Types Depending on Deck Positions



• Bridge Types Depending on Support Types





- 해석이 복잡함, n 경간 연속교



<u>Gerber(게르버) Bridge</u>

- Adding hinges to the continuous span bridge to convert "indeterminate" to "determinate" - 구조해석이 쉬우나 힌지 사이의 보가 과다하게 처지는 문제가 있음

• Bridge Types Depending on Deck Types



RC 슬래브교

RC Slab Bridge Should avoid long-length due to increase self-load



중공 슬래브교

Hollow Slab Bridge Reduce self-load with holes

<u>Slab bridge</u>

- Slab top structure: short-length span (single span: 5-15m, continuous span: 10-30m)

- Low-height top structure (1/16-1/20 of the bridge length)



Rahmen(Rigid-Frame) Bridge

- Connected top and bottom structures
- Economical with low-pier-height and short-span bridges
- No need for expansion joints till 50m
- Spaces under the bridge for overpass road or river crossing
- Easy maintenance, good appearance

The weight of the girder pushes straight down on the piers

• Bridge Types Depending on Deck Types: Girder Bridge





(b) Double T형교





(a) **직사각형**







<u>T-Shape (T 형교)</u>

- Usually used for short spans (30m)
- Less self-load than slab bridges
- <u>Double T-shape</u>: 50m span with prestress, horizontal tendons due to a big gap b/w girders

GIRDER BRIDGE

<u>Plate Girder (강판형교)</u>

- Use I-shape steel girder (50m)
- Require many steel members, complicated
- Low horizontal strength \rightarrow weak for curved roads

<u>Plate Box Girder (강상형교)</u>

- Widely used (50-60m)
- Good for curved and widened roads
- Steel box is prefabricated, bolted and welded in the field \rightarrow fast, easy construction







진도대교 강상판

완도-신지도 연도교

부산남항대교

Bridge Types Depending on Deck Types: Girder Bridge



<u>Steel Plate Box Girder (강상판형교)</u>

- Steel-plate slabs \rightarrow smaller self-load \rightarrow longer span (70-80m)
- Expensive due to many steel members
- Complicated field welding of the steel plate, more vibration than concrete slab







그림. 프리플렉스교량

PSC Beam

- Use pre-stressed concrete girder (20-40m)
- Cheaper construction

- 2m bottom structure for 30m span \rightarrow require enough bottom spaces \rightarrow For the limited spaces, use preflex bridges with I beam

TRUSS BRIDGE

Bridge Types

Girder bridge strengthened by trusses Lighter than ordinary girder sections of equal length

• Bridge Types Depending on Deck Types: Truss Bridge



Component parts of a typical truss bridge - Isometric View ¹















Pratt Truss

K Truss







XR



Howe Truss



Baltimore Truss

ARCH BRIDGE

Instead of pushing straight down, the weight of an arch bridge is carried outward along the curve of the arch to the supports (abutments) at each end

Bridge Types Depending on Deck Types: Arch Bridge





2-Hinged Arch Widely used, Good appearance and economical Applicable to sound ground conditions Applicable to over 300m with truss braced ribs





3-Hinged Arch Possible deflection in the center hinge Less durability, Not used that much



Bridge Types







Fixed Arch Most economical arch Higher fixed moment \rightarrow for sound ground conditions *Less deflection due to higher durability* Usually used for concrete bridge (difficult to apply hinges)

Tied Arch Less horizontal loads to the tie \rightarrow Applicable to poor ground conditions Bigger loads to arch rib \rightarrow Bigger rib thickness are used thus less economical

- Bridge Types Depending on Deck Types: Cable Stayed Bridge (사장교)
 - The cables are attached to the towers, which alone bear the load
 - For long-span bridges, self-load becomes bigger thus need supports by the tower
 - In a radial pattern, cables extend from several points on the road to a single point at the top of the tower
 - In a parallel pattern, cables are attached at different heights along the tower, running parallel to one other.



- Bridge Types Depending on Deck Types: Suspension Bridge (현수교)
 - The cables ride freely across the towers, transmitting the load to the anchorages at either end which are imbedded in either solid rock or massive concrete blocks
 - Aesthetic, light and strong, but most expensive to build





그림. 타정식 현수교(광안대교)





그림. 자정식 현수교(영종대교)

<u>Earth-Anchored(타정식)</u>

- The cables are fixed to anchorages
- No effect to stiffening girder (보강형) thus easier structural analysis and design
- Require big mass of anchorage \rightarrow less attractive, more expensive with poor ground conditions

<u>Self-Anchored(자정식)</u>

- Directly fix cables into the stiffening girder
- Complicated structural analysis and design
- No need for the large anchorage

• Bottom Structure: Pier (교각)

 When constructing many piers in the river, it reduces the cross section area of the river, which increases fluid velocity and scouring. To prevent flood, the cross section of pier needs to be designed as circular or oval shapes



(a) 기초 콘크리트



(b) 교각 콘크리트





(c) 코핑부 콘크리트

(d) 교각 시공 완료

• Bottom Structure: Pier

- Sliding Form

- Assemble the concrete form at the bottom at the beginning and continuously lift the form to the top without form removal by using hydraulic jacks
- Once the concrete is cured and reach the desired strength without deformation, the form moves up to the next height
- Possible to construct 1 story each day
- Good for chimney, cooling tower, silo, pier, bridge tower, etc.
- No connection line, save form disposal, improve worker safety
- No stop from the bottom to the top: 24-hour working, require accurate skills and construction methods (no cold joint), not economical for the short height





• Climbing Form



- Bottom Structure: Pier
 - Climbing Form
 - Similar concept with the sliding form, but remove forms for each story and do not use hydraulic jacks (normally use tower crane)
 - Takes longer time (5-6 days for 1 story)
 - One form unit is about 4-6m
 - Uniform placement height, more traditional method that is more familiar with workers → good productivity
 - Equipment cost, safety risks at the high height (e.g., wind) especially for form removal operation, falling risk of workers working in gang forms



- Top Structure: FSM (Full Staging Method, 동바리공법)
 - For good ground strength and short height bridges
 - Install supports to the entire span to bear loading of concrete, forms, and working platform

Fixed Supports



Movable Supports





<u>Whole Support (전체지지식)</u>

- Flat ground and smaller than 10m height
- Simple installation and easy construction
- Steel or wood supports evenly bear the distributed loads of the top structure
- Need for no concentrated loading during concrete placement

• Top Structure: FSM (Full Staging Method, 동바리공법)



<u>Pillar Support (지주지지식)</u>

- Uneven ground and obstacles on the ground
- Larger than 10m height
- For poor grounds, need to drive piles



<u>Girder Support (거더지지식)</u>

- River having poor ground condition
- When difficult to install supports between spans
- For the cross section bridges
- When needs to use the under spaces
- For large height bridges

- Top Structure: FCM (Free Cantilever Method, 캔틸레버공법)
 - Use form traveler or moving gantry to balance left and righthand sides of the bridge instead of installing supports and construct 2-5m girders step-by-step
 - When support installation is difficult
 - Used for PC box girder, suspended, arch bridges



*Sheath pipe: for inserting steel strands to apply prestress





- Top Structure: FCM (Free Cantilever Method, 캔틸레버공법)
 - Super-capital (주두부) construction: about 90 days



(a) Footing 상면 고르기



(b) 동바리 설치



(c) 동바리/받침보 설치



(d) 측면 거푸집 설치



(h) Air Vent 설치



(1) 주두부 거푸집 해체



(e) 측면부 철근 쉬스관 설치



(i) 슬래브 콘크리트 타설



(j(k) 인장 Jack 설치



(k) 주두부 설치









덕적~소야간 연도교 건설공사 기본 및 실시설계 강연선 배치 개요도 배치 개요도 8=1:500 8년 11 2011 2011 11 2011 11 2011 11 201			
87,410 15,510 3,000 1064.750-67,500 465,500 5,000 5,000 (F9I 72)) (F9I 72)) (F9I 72)) (SH 7	314.820 140.000 465.500 1064.750-47.500 3.000 14.000 107 107 107 107 107 107 107	064.750-47.500 465.500 5.000 5.00 -14.000 -140.000 -140.000 -140.000 01 -140.000 -100 -100 101 102 -110 -110 101 100 -110 -110 101 100 -110 -110 101 100 -110 -110 101 100 -110 -110 101 100 -110 -110 101 100 -110 -110 101 100 -110 -110 101 100 -110 -110 101 -110 -110 -110 101 -110 -110 -110 101 -110 -110 -110 101 -110 -110 -110 101 -110 -110 -110 101 -110 -110 -110 101 -110 -110 -110	67.410 485.500 1064.750-47.500 3.000 15.5H0 (FSH 722) 107 107 107 107 107 107 107 107
해당 변지 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	815 831 (8)年早 200(名) 00.6 ² -166A		정착구 보강 상세도 MCIONAGE HEAD
강선범호 강선필이(8) 해당긴장길이(8) 핸던가수(EA) 백트길이(8) 총 관선필이(8) 한 전장하구 개수(EA) 고정정하구 개수(EA) TC1 14.000 2 4 56.000 94.000 4 4 TC2 14.000 2 4 56.000 94.000 4 4 TC3 121.000 2 4 56.000 94.000 4 4 TC3 121.000 2 4 162.000 8 0 TC4 28.000 2 4 112.000 186.000 8 0 TC5 35.000 2 4 186.000 176.000 8 0 TC6 42.000 2 4 186.000 176.000 8 0 TC7 51.500 2 4 284.000 282.000 8 0 TC8 61.000 2 4 284.000 282.000 8 0 TC8 61.000 2 4 282.000 8	강선번호 강성일이(10) 허유킹장길이(10) 행경 BT1 22.000 2 2 44.000 - BT2 31.500 2 2 63.000 - BT3 41.000 2 2 82.000 - BT4 50.500 2 2 101.000 - BT5 60.000 2 2 101.000 - BT1 1850 0.2 4 74.000 - BT11 18.500 2 4 74.000 - BT11 287.750 2 4 107.000 - BT13 42.750 2 4 107.000 - BT14 47.500 2 4 100.000 -	[길이(M) 인장정착구 개수(EA) 고정정착구 개수(EA) .000 4 0 .000 4 0 .000 4 0 .000 4 0 .000 4 0 .000 4 0 .000 4 4 .000 4 4 .000 4 4 .000 4 4 .000 4 4	(교왕진세) (전5TING 0600-300 (가 5PIRAL BAR H19 (교왕진세) (교왕진세) (전 호 직 경 길 이 (4)) 전 수 휴일이(4) 단위당권 추중명(TONF) 비 고 (4) 10.640 200 21280 000 14,788 4,1801 * 제 2128.000 2.250 4.788 * 제 4.788 4,1801
ICITI es.soo 2 4 388.000 388.000 8 0 TG12 99.000 2 4 388.000 494.000 8 0 TG13 108.500 2 4 438.000 494.000 8 0 TG13 108.500 2 4 454.000 494.000 8 0 TG14 118.000 2 4 451.000 480.000 8 0 TG15 127.500 2 4 516.000 516.000 8 0 TG16 137.000 2 4 549.000 556.000 8 0 SP1 157.000 2 4 548.000 556.000 8 0 SP1 157.000 2 4 548.000 556.000 8 0 - - - 4634.000 5670.000 128 8	3882 47.600 2 4 100.600 1 ★9-74 1282.000 1 389-74 1282.000 1	0.000 <u>4 4</u> 6.000 <u>44</u> 20 <u>-</u>	2. 김스트의 이상의 적사 (손실상 신속 체용)가수는 다음과 같다. 실부 : 국용가원계수(2,5/4,50)가(4) 귀성이원칙수(5,0005/6,5,1)만왕(56) 지하되도록 체공하기수(2,5/4,50)가(4) 관광이는 구조계산은 실시하고 이상이 일을 장하여 김목원의 승인을 두한후 시용한다. 4. 형작구 표시기호 의원 정착구 오 전 전부 고정 정착구 오 한단 긴장 이 가지 가지 않는 1,300 분위 도입 강의 : 주도부 – 실부: [* 0,75 (6 = 1,425 분위 주도부 위 _ 라부: [* 0,72 (6 = 1,308 분위 5. 강인성 길이 산출시 일단긴장은 여유길이를 2,04로 적용
인선광역시 공신군 <u>기법 8</u> 적학으로 전공 2017 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	· 스 · · · · · · · · · · · · · · · · · ·	조충영 선 소火 김홍식 상분 명 과업해외자 분이별해외자	비시 8 고 도면 명 강연선 배치 개요도 양병홍 // 1 축 척 S=1:NONE 편철번호 8.035



- Top Structure: FCM (Free Cantilever Method, 캔틸레버공법)
 - Segment Construction (Form Traveler Installation)



Design: 1 month, Manufacturing: 3 months, Installation: 1 months

- Top Structure: FCM (Free Cantilever Method, 캔틸레버공법)
 - Segment Construction (Form Traveler)
 - Normal segment span: 3-5m
 - Concrete placement: low fringe through the opening of the bottom plate → Connection b/w the low fringe and the body → Body → Cantilever → Top plate → Connection b/w the top plate and the body
 - Key segment: connection b/w segments



Segment Construction: form setting (2 days), rebar and formwork (3 days), concrete placement (1 day), Curing and tensioning (4 days), Form Traveler detachment (2 days) Side Span Structure (측경간단부): 20 days for 7m

Bridge Construction

Key Segment: 20 days

- Top Structure: FCM (Free Cantilever Method, 캔틸레버공법)
 - Segment Construction (Form Traveler)



① 이동식 거푸집 설치



② 이동식 거푸집 조립



③ 세그먼트 철근 조립



④ 콘크리트 타설



⑤ 세그먼트 인장



1 키 세그먼트 강봉 인장 ⑨ 키 세그먼트 철근 조립



⑥ 세그먼트 그라우팅



⑦ 강연선/lifting collar 설치



① 키 세그먼트 콘크리트 타설



12 키 세그먼트 연결

- ⑧ 키 세그먼트 수평버팀 설치

 Top Structure: MSS (Movable Scaffolding System, 이동식 비계공법)



 Top Structure: MSS (Movable Scaffolding System, 이동식 비계공법)



- Top Structure: MSS (Movable Scaffolding System, 이동식 비계공법)
 - Install forms on the movable scaffolding structure and place concrete
 - Above type: hang forms to the above scaffolding structure



- Below type: structure supports forms



- Top Structure: MSS (Movable Scaffolding System, 이동식 비계공법)
 - Advantages
 - Fast, safe, and productive construction
 - Less labor input and construction under rainy weather if roof is installed
 - Reusable forms and scaffolds
 - Disadvantages
 - Expensive manufacturing of the system
 - Difficult applicable to curved and changeable cross sections

Top Structure: MSS (Movable Scaffolding System, 이동식 비계공법)



① 교각 브래킷 설치



② 가벤트 설치



③박스 거더/세로 빔 설치



⑦ 하부 VENT 호스 설치



① 그라우팅 작업



④ MSS 거푸집 설치



⑧ 상부 철근 조립



12 MSS launching



⑤ 하부 철근 조립



⑨ 상부 콘크리트 타설











• Top Structure: MSS (Movable Scaffolding System, 이동식 비계공법)



- Place concrete while checking the left-right balance to prevent twisting
- For 1 span: Concrete placement (1 day) → Concrete curing (3 days) →
 Tensioning and detaching MSS (1 day) → Moving MSS (1 day) → Outer
 form placement (2 days) → Strand, rebar, inner form placement (5 days)
- System design and manufacturing (3 months), installation at field (1.5 month)